

CB1E 齿轮泵

GROUP1 EUROPEAN STYLE GEAR PUMPS

德力液压 Deli®

简介 General Description

CB1E 齿轮泵系高压小排量齿轮油泵，由一对高强度齿轮、轴套、泵体、前盖、后盖 等主要部件组成，轴向间隙由高精度浮动轴套自动补偿，使得 CB1E 齿轮泵具有高的机械效率和容积效率，该泵噪音低、可靠性高，广泛应用于卡车液压系统，举升和传送机械，矿山机械，农业机械等。


The CB1E gear pump consists of a gear pair supported by two aluminum bearing blocks, a housing, front cover and rear cover. The axial clearance can be automatically compensated by the bearing blocks. The CB1E pump features are simple structure, high mechanical and volumetric efficiency, low noise level as well as high reliability. It is widely used in the hydraulic system of truck, lift and transport machinery, mining machine, and agriculture, etc.

型谱 Order Code

CB1E - F * * * *	
额定压力 Rated pressure	20MPa
排量 Displacement	1.3 to 13 ml/r (0.0830 to 0.8348 in³/r)
轴端形式 Shaft Option	B 扁尾 Tang E 半圆键 Whitney Key
旋向 Direction	空白 Omit 右旋 CW F 左旋 CCW
进出油口 Port Configurations	C 法兰孔连接 Flange A 管螺纹 Gas Threaded Ports(BSPP)



外形尺寸图 Outline Dimension



技术参数 Technical Data

Model 型号	Displacement 排量 mL/r(in³/r)	Pressure Pressure			Speed Speed		Dimension 尺寸 Dimension							
		P1 MPa	P2 MPa	P3 MPa	Rated RPM	Max RPM	L mm	M mm	G 螺纹型进出油口 Inlet Outlet		法兰型进出油口 Inlet Outlet			
									进油口 Inlet	出油口 Outlet	进油口 Inlet	出油口 Outlet		
CB1E-F1.3*	1.36 (0.083)	20	25	28	2000	4000	40	79	G1/2	G3/8	φ 13	φ 13		
CB1E-F2 *	2.05 (0.125)						41	81						
CB1E-F2.7*	2.74 (0.167)						42	83						
CB1E-F3.2 *	3.42 (0.209)						43	85						
CB1E-F4 *	4.10 (0.250)						44	87	G1/2	G1/2				
CB1E-F5 *	5.13 (0.313)						45.5	90						
CB1E-F6 *	6.16 (0.376)						47	93						
CB1E-F7.5 *	7.52 (0.459)						3500	49	97					
CB1E-F9 *	9.23 (0.563)	18	20	22	3000	2500	51.5	102						
CB1E-F10 *	10.95 (0.668)						54	107						
CB1E-F13 *	13.68 (0.835)						2000	58	115					